



minipack® - torre
Packaging machines and systems

TUNNEL 50 TWIN

FLEXIBLE AND UPDATED SOLUTIONS TO GET THE BEST PACKAGING



DESCRIPTION

TUNNEL 50 TWIN has been designed to solve the needs to pack small product at high speed with great technical and esthetical results. Double heating chamber, double heating regulation, excellent thermal insulation, high speed belt and high speed shrink, great air flow control makes this machine the perfect tool to solve any kind of shrink problem with the maximum efficacy.

TECHNICAL FEATURES

Electrical power supply	V	200/208/220/380
Phase	ph	3

minipack®-torre S.p.A.

Sede legale - Via Provinciale, 54 - 24044 DALMINE (BG) Italy

P.IVA - C.F.: 01633550163 - Capitale sociale 619.200,00 i.v. - Reg. Imprese di Bergamo 01633550163 - REA n. 224151



minipack®- torre
Packaging machines and systems

MAX power installed	kW	13.2
MAX product size	mm	400x190x lg. 1140
Machine dimensions	mm	2130x800x h. 1460
Machine weight (Net/Gross)	kg	260/318
Tunnel infeed dimensions	mm	450x210

minipack®-torre shall not be held liable for typos or printing errors in this catalogue. It also reserves the right to make changes to the specified features without prior notice. All trademarks are property of their respective owners and are hereby acknowledged.

minipack®-torre S.p.A.

Sede legale - Via Provinciale, 54 - 24044 DALMINE (BG) Italy

P.IVA - C.F.: 01633550163 - Capitale sociale 619.200,00 i.v. - Reg. Imprese di Bergamo 01633550163 - REA n. 224151